# QuantaGrid D51PS-1U

Powerful Compact 2-Socket Server





QuantaGrid D51PS-1U is a compact but powerful 2-Socket server.Based on the Intel® Xeon® processor E5-2600 v3 product family, it delivers enterprise-grade performance with up to x16 DDR4 memory. It i's an ideal front-end web, data -caching, search and application server.

#### **Ultra Dense Short Chassis**

QuantaGrid D51PS-1U supports dual CPU, 16 DRAM, two PCIe expansion devices and two PSUs in a 24" deep chassis.As a short form factor, this server can be deployed in almost any SMB or data center environment.

### Affordable Enterprise Class Performance and Reliability

The D51PS-1U delivers enterprise- class performance based on the latest Intel® Xeon® processor E5-2600 v3 product family and DDR4 memory technology.Despite its compact size, it retains scalability and reliability.It offers necessary LAN and storage expansion flexibility without superfluous configuration options. The D51PS-1U can accommodate one PCle x8 OCP mezzanine plus one PCle x8 QCT LAN or SAS mezzanine (adding up to eight GbE ports in a 1U chassis) .The server supports fan and PSU redundancy to maintain reliable application performance even if one of these critical components fails.

#### Flexible and Scalable I/O options

QuantaGrid D51PS-1U provides flexible I/O

- Ultra Dense Short Chassis
- Affordable Enterprise Class Performance and Reliability
- Flexible and Scalable I/O options



Rear view

scalability for today's diverse data center application requirements. It features OCP LAN mezzanine card solutions in addition to dual GbE or quad 1GbE LAN on motherboards (LoM). With various controller vendors and different speed and technology options, customers can choose from 1GbE to 56GbE bandwidth, copper or fiber-optic cabling, basic Ethernet function or FCoE and ISCI SAN connectivity. The onboard SAS controller offers multiple Quanta SAS mezzanine card options with different RAID levels and data transfer bandwidth so customers can tailor the SAS controller for specific application needs.

#### **About QCT**

QCT (Quanta Cloud Technology) is a global datacenter solution provider extending the power of hyperscale datacenter design in standard and open SKUs to all datacenter customers.

Product lines include servers, storage, network switches, integrated rack systems and cloud solutions, all delivering hyperscale efficiency, scalability, reliability, manageability, serviceability and optimized performance for each workload.

QCT offers a full spectrum of datacenter products and services from engineering, integration and optimization to global supply chain support, all under one roof

The parent of QCT is Quanta Computer Inc., a Fortune Global 500 technology engineering and manufacturing company.

http://www.QCT.io



## QuantaGrid D51PS-1U



#### Found at: www.QCT.io/wheretobuy

**United States** 

QCT LLC., Silicon Valley office

1010 Rincon Circle, San Jose, CA 95131 TOLL-FREE: 1-855-QCT-MUST TEL: +1-510-270-6111 FAX: +1-510-270-6161 Support: +1-510-270-6216

China

云达科技,北京办公室 (Quanta Cloud Technology) 北京市朝阳区东三环中路 1号 环球金融中心东楼 1508 室 TEL: +86-10-5920-7600 FAX: +86-10-5981-7958

云达科技,杭州办公室

(Quanta Cloud Technology) 浙江省杭州市西湖区古墩路浙商财富中心 4 号楼 303 室

TEL: +86-571-2819-8650

Japan

Quanta Cloud Technology Japan 株式会社 日本国東京都港区芝大門二丁目五番八号 牧田ビル3階

TEL: +81-3-5777-0818 FAX: +81-3-5777-0819

雲達科技 (Quanta Cloud Technology) 桃園市龜山區文化二路 211 號 1 樓

TEL: +886-3-286-0707 FAX: +886-3-327-0001

Other regions

Quanta Cloud Technology

No. 211 Wenhua 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan TEL: +886-3-327-2345

FAX: +886-3-397-4770


QCT authorized partner

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their representative holders.
Copyright © 2014-2015 Quanta Computer Inc. All rights reserved.

Processor	Processor Type: Intel® Xeon® processor E5-2600 v3 product family
	Max. TDP Support: 135W
	Number of Processors: 2
	Internal Interconnect: 6.4 / 8.0/ 9.6 GT/s
Chinas	L3 Cache: Up to 45MB
Chipset	Intel® C610
Memory	Total Slots: 16
	Capacity:
	Up to 512GB RDIMM
	Up to 1024GB LRDIMM
	Memory Type: 2133 MHz DDR4 RDIMM/ LRDIMM
	Memory Size:
	32GB, 16GB, 8GB RDIMM
	64GB, 32GB LRDIMM
Network	LOM:
Controller	Intel® I350 dual-port 1 GbE
	Dedicated 1 GbE management port
	Optional NIC (more options refer to the CCL):
<u></u>	Please refer to our Compatible Component List for more information
Storage	Onboard:
Controller	Intel® 610:
	(10) SATA 6Gb/s ports
	SATA RAID 0, 1, 10
	Optional Controller (more options refer to the CCL):
O de la colonia de la colonia	Please refer to our Compatible Component List for more information
	Support (2) SATADOM
Video	Integrated AST2400 with 8MB DDR3 video memory
Rear I/O	(2) USB 3.0 ports
	(1) VGA port
	(1) RS232 serial Port
	(2) 1 GbE RJ45 port
	(1) GbE RJ45 management port
TDIA	(1) ID LED
TPM	Yes (With TPM 1.2/ 2.0 option)
Form Factor	1U Rack Mount
Dimensions	W x H x D (inch): 17.244 x 1.75 x 24
Chausan	W x H x D (mm): 438 x 43.2 x 609.6
Storage	Option 1: (10) 2.5" hot-plug
	Option 2: (4) 3.5" hot-plug , (2) 2.5" fixed SSD
Expansion Slot	Option 1 (default):
	(1) PCle Gen3 x8 SAS mezzanine slot
	(1) PCle Gen3 x16 OCP LAN mezzanine slot
	Option 2:
	(1) PCIe Gen3 x8 Quanta LAN mezzanine slot
Fuert I/O	(1) PCIe Gen3 x16 OCP LAN mezzanine slot
Front I/O	2.5" SKU: None
n	3.5" SKU: (2) USB 2.0 ports
Power Supply	1+1 High efficiency redundant hot-plug PSU
	(default with one PSU only; detailed PSU options please refer to "ordering info" or
<b>-</b>	"CCL")
Fan	(5) dual rotor fans (9+1 redundant)
System	IPMI v2.0 Compliant, on board "KVM over IP" support
Management	Quanta Datacenter Manager 2.0/ QDCM 2.0 (Optional)
Operating	Operating temperature: 5°C to 40°C (41°F to 104°F)
Environment	Non-operating temperature: -40°C to 65°C (-40°F to 149°F)
	Operating relative humidity: 20% to 85%RH.
	Non-operating relative humidity: 10% to 90%RH



Intel, the Intel logo, Xeon, and Xeon Inside are trademarks or registered trademarks of Intel Corporation in the U.S. and/or other countries.

