



QuantaGrid D52B-1U

Defying Physical Limitations

- **Ultimate Compute and Storage Density**
- **Flexible and Scalable I/O options**
- **Tool-less HDD/SSD Tray and PCIe Riser Module**
- **Quick Deployment and Maintenance**

About QCT

Quanta Cloud Technology (QCT) is a global datacenter solution provider. We combine the efficiency of hyperscale hardware with infrastructure software from a diversity of industry leaders to solve next-generation datacenter design and operation challenges. QCT serves cloud service providers, telecoms and enterprises running public, hybrid and private clouds.

Product lines include hyper-converged and software-defined datacenter solutions as well as servers, storage, switches, integrated racks with a diverse ecosystem of hardware component and software partners. QCT designs, manufactures, integrates and services cutting edge offerings via its own global network. The parent of QCT is Quanta Computer, Inc., a Fortune Global 500 corporation.

Found at: www.QCT.io/wheretobuy



Intel Inside®. New Possibilities Outside.



Rear view

Unleashing Computing Performance

- Faster socket interconnect, 1.5x memory bandwidth and 2x FLOPs peak performance capability with Intel® Xeon® Processor Scalable Family.
- Up to 112 vCPUs per server and 3.9x higher virtualized throughput compared to previous platforms based on the Intel® Xeon® processor E5.




Flexible and Scalable Configurations for Hyperconverged Datacenters




- Up to 5 PCIe expansion slots in a 1U chassis
- Flexible I/O options, including a variety of SAS mezz and OCP NIC/PHY mezz options, so users avoid the extra expense of unnecessary LOM or RAID controllers.
- Three different kinds of storage configurations, including LFF+SSD Hybrid, SFF (SATA+U.2) Tiered and the industry's first 12x U.2 All Flash, tailored for diversified software-defined workloads.
- Optional SATADOM or M.2 SSD for OS installation.

Sophisticated Power and Thermal Design to Avoid Unnecessary OPEX

- Minimized power consumption during system idle mode.
- Support for the industry's most efficient 80 Plus Titanium PSU options.
- Precise power and airflow distribution to ensure performance stability under all levels of system loading.



Quick Deployment and Maintenance



- Tool-less HDD, fan, PCIe card exchange
- Optional MicroSD card to record system health logs without opening the chassis even when powered-off
- Intuitive data center management with QCT System Manager (QSM) via integration with industry standard RESTful API and Intel® Rack Scale Design (RSD).



QuantaGrid D52B-1U Specifications

Processor	Processor Type: Intel® Xeon® Processor Scalable Family Max. TDP Support: 165W (Refer to CCL) Number of Processors: 2 Processors Internal Interconnect: 9.6/10.4 GT/s		
Form Factor	1U		
Dimensions	W x H x D (inch): 17.3 x 1.7 x 30.7 W x H x D (mm): 440 x 43.2 x 780		
Chipset	Intel® C621, Intel® C624		
Storage	Default Configuration: NVMe support, 2.5" Hot-plug, 3.5" Hot-plug		
SKU - #1 [All Flash SKU]: (12) 2.5" hot-plug SATA/ NVMe SSD	SKU - #2 [SFF Tiered SKU]: (8) 2.5" hot-plug SATA/SAS drives + (4) 2.5" hot-plug NVMe/SATA/SAS drives	SKU - #3 [Hybrid SKU]: Option 1 : (4) 3.5"/2.5" hot-plug SATA/SAS drives, (4) 9mm NVMe/SATA/SAS drives (optional) Option 2 : (4) 3.5"/2.5" hot-plug SATA/SAS drives, (4) 9mm SATA/SAS drives (optional)	
Memory	Total Slots: 24 Capacity: Up to 3TB (128Gx24) of memory for RDIMM/LRDIMM Memory Type: 2666 MHz DDR4 RDIMM Memory Size: 64GB, 32GB, 16GB, 8GB RDIMM (Refer to CCL)		
Expansion Slot	SKU - #1 [All Flash SKU]: (1) PCIe Gen3 x16 OCP 2.0 mezzanine slot or PHY card (1) PCIe Gen3 x16 LP MD-2 (1) PCIe Gen3 x8 FHHL	SKU - #2 [SFF Tiered SKU]: Option 1 (3PCIe) (1) PCIe Gen3 x16 SAS mezzanine slot (1) PCIe Gen3 x16 OCP 2.0 mezzanine slot or PHY card (1) PCIe Gen3 x16 LP MD-2 (2) PCIe Gen3 x 8 LP MD-2 Option 2 (2PCIe) (1) PCIe Gen3 x16 SAS mezzanine slot (1) PCIe Gen3 x16 OCP 2.0 mezzanine slot or PHY card (1) PCIe Gen3 x 8 FHHL (1) PCIe Gen3 x16 LP MD-2	SKU - #3 [Hybrid SKU]: Option 1 (3PCIe) (1) PCIe Gen3 x16 SAS mezzanine slot (1) PCIe Gen3 x16 OCP 2.0 mezzanine slot or PHY card (1) PCIe Gen3 x16 LP MD-2 (2) PCIe Gen3 x 8 LP MD-2 Option 2 (2PCIe) (1) PCIe Gen3 x16 SAS mezzanine slot (1) PCIe Gen3 x16 OCP 2.0 mezzanine slot or PHY card (1) PCIe Gen3 x16 FHHL (1) PCIe Gen3 x16 LP MD-2
Network Controller	LOM: Dedicated (1) GbE management port Optional NIC: Quanta Intel® X527 10G SFP+ dual/quad-port OCP PHY mezzanine or Quanta Intel® X557 10G RJ45 dual/quad-port OCP PHY mezzanine or Quanta Intel® I357 1G RJ45 dual/quad-port OCP PHY mezzanine or (more options refer to the CCL)		
Front I/O	(2) USB 3.0 ports Power/ID/Reset Buttons Power/ID/Status LEDs		
Storage Controller	Onboard: Intel® 621/ 624: 14x SATA 6Gb/s ports SATA RAID 0, 1, 10 Optional Controller: Quanta LSI® 3216 12Gb/s SAS mezzanine Quanta LSI® 3516 12Gb/s SAS mezzanine (RAID 0,1,5,6,10,50,60) Intel® VROC Upgrade Module for PCIe SSD (2) PCIe M.2 support with M.2 adapter for boot optimization (option)		
Power Supply	(1+1) High efficiency redundant hot-plug Platinum/Titanium 500W/800W* PSU (detailed PSU options please refer to "ordering info" or "CCL")		
Onboard Storage	(2) SATADOM (option)		
Fan	(8) dual rotor fans (15+1 redundant)		
Video	Integrated ASPEED AST2500 8MB DDR4 video memory		
System Management	Redfish v2.1 IPMI v2.0 Compliant, on board "KVM over IP" support QCT System Manager (QSM) v1.8 (Optional)		
Rear I/O	(2) USB 3.0 ports (1) VGA port (1) RS232 serial port (1) GbE RJ45 management port (1) ID LED (1) MicroSD slot		
Operating Environment	Operating temperature: 5°C to 40°C (can support 45°C under certain situation) Non-operating temperature: -40°C to 70°C Operating relative humidity: 20% to 85%RH Non-operating relative humidity: 10% to 95%RH		
TPM	TPM 1.2/2.0 SPI module		
Weight (Max. Configuration)	20.7 KG		



Found at:
www.QCT.io/wheretobuy

All specifications and figures are subject to change without prior notice. Actual products may look different from the photos.

QCT, the QCT logo, Rackgo, Quanta, and the Quanta logo are trademarks or registered trademarks of Quanta Computer Inc.

All trademarks and logos are the properties of their respective holders.

Copyright © 2017 Quanta Computer Inc. All rights reserved.

United States
 QCT LLC., Silicon Valley office
 1010 Rincon Circle, San Jose, CA 95131
 TOLL-FREE: 1-855-QCT-MUST
 TEL: +1-510-270-6111
 FAX: +1-510-270-6161
 Support: +1-510-270-6216

Japan
 Quanta Cloud Technology Japan 株式会社
 日本国東京都港区芝大門二丁目五番八号
 牧田ビル 3 階
 TEL: +81-3-5777-0818
 FAX: +81-3-5777-0819

Germany
 Quanta Cloud Technology Germany GmbH
 Hamborner Str. 55, 40472 Düsseldorf
 TEL: +49-2405-4083-1300

Other regions
 Quanta Cloud Technology
 No. 211 Wenhua 2nd Rd., Guishan Dist.,
 Taoyuan City 33377, Taiwan
 TEL: +886-3-327-2345
 FAX: +886-3-397-4770



Intel Inside®.
New Possibilities Outside.

Intel, the Intel logo, Xeon, and Xeon Inside are trademarks or registered trademarks of Intel Corporation in the U.S. and/or other countries.